DIASEN

Certified B Corporation

DECLARATION OF PERFORMANCE

Product identification code 198/2026 - DP194EN26100501-1

1. Unique identification code of the product-type: **Diathonite Thermactive**.
2. Intended uses: **Designed general purpose rendering/plastering mortar for external and internal use on walls, ceilings, columns and partitions**.
3. Manufacturer: **Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) – www.diasen.com**
4. Systems of AVCP: **System 4.**
5. Harmonized standards: **EN 998-1:2016.**
   Notified bodies: **No tasks for the notified body**
6. Performances declared:

Essential characteristics	Performance	Reference standard
Reaction to fire	Class A1	UNI EN 13501-1
Water absorption	NPD	UNI EN 1015-18
Water vapour permeability	μ = 3	UNI EN 1015-19
Adhesion	NPD	UNI EN 1015-12
Thermal conductivity ($\lambda_{10,\ dry}$)	0,035 W/mK	UNI EN 12667 (HFM)
Durability	NPD	UNI EN 1015-21
Compressive strength	2,80 N/mm²	UNI EN 1015-11
Dry bulk density	250 ± 15%	UNI EN 1015-10
Dangerous substances	See SDS	Regulation CE 878/2020

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Diego Mingarelli (Legal Representative)**
Sassoferrato, 05/10/2026

DIASEN
DIASEN SRL UNIPERSONALE - Società Benefit
Z.I. Berbentina, 5 60041 Sassoferrato (AN)
P.IVA 01553210426

DIASEN

Certified B Corporation

CE

DIASEN

Zona Industriale Berbentina, 5 – 60041
Sassoferrato (AN) – Italy
www.diasen.com

20
EN 998-1
C.I.P.198/2026
DIATHONITE THERMACTIVE

Designed general purpose rendering/plastering mortar for external and internal use on walls, ceilings, columns and partitions.

Reaction to fire	Class A1	UNI EN 13501-1
Water absorption	NPD	UNI EN 1015-18
Water vapour permeability	μ = 3	UNI EN 1015-19
Adhesion	NPD	UNI EN 1015-12
Thermal conductivity ($\lambda_{10,\ dry}$)	0,035 W/mK	UNI EN 12667 (HFM)
Durability	NPD	UNI EN 1015-21
Compressive strength	2,80 N/mm²	UNI EN 1015-11
Dry bulk density	250 ± 15%	UNI EN 1015-10
Dangerous substances	See SDS	Regulation CE 878/2020

DIASEN supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*